

**EPSON**<sup>®</sup>  
EXCEED YOUR VISION



*Epson*  
*EMP* **750/755**



Professional, compact  
and portable 3LCD projectors

The lightweight and compact Epson EMP-750/755 projectors enable you to give high quality, mobile presentations at an affordable price. With our innovative quick start and instant off functions, presenting on the move has never been quicker or easier.

**Designed for the presenter on the move**

These ultra-light, compact projectors weigh in at under 1.8kg, and come with a stylish carrying case to make travelling easy. With the Epson EMP-755 you don't even need to bring your laptop to the meeting. Simply save your presentation onto a standard memory device\* using the included SlideMaker software, insert it into the projector and you can run your presentation straight away.

**Ready in seconds**

To use the Epson EMP-750/755 projectors all you need to do is plug in and project. Within 7 seconds your projector is warmed up and ready to go. Your projected image is instantly aligned thanks to the automatic vertical keystone function giving +/- 30 degrees correction, whilst the level of projection can be easily adjusted with the single foot release lever.

\* USB memory stick or various flash media types using PCMCIA adaptor (not included)

What's more, when you have finished your presentation, just switch off and pack away. You won't need to wait around for your projector to cool down thanks to our innovative one touch off function. It couldn't be easier or quicker.



**Single foot release lever**

Easily adjust the projection level using the single foot release lever.



### Clear images under any condition

Whatever the size of the room or the light conditions, you can be confident that the Epson EMP-750/755 projectors will reproduce astoundingly beautiful images in bright, natural colours with no flicker or colour break-up. You can project a perfect 60" image from as little as 2 metres away from the screen. Thanks to the 2000 ANSI lumens output and advanced 3LCD technology the image will stay bright and clear even in high ambient light conditions. The high brightness is achieved through Epson's exclusive E-TORL lamp which efficiently gathers light and eliminates light leakage and diffraction, resulting in a longer lamp life and lower power consumption.

### Complete flexibility

The Epson EMP-755 projector comes equipped with Epson's EasyMP technology so you can use it just as well in the office as on the road. Simply connect to your network using standard cables and an optional network card, or use the included wireless card to achieve fast secure wireless transmission. In both cases you can present data, video and presentations and can also manage your projector remotely.

### Instant Off

No cool down time needed – just switch off and pack away!



### Control panel

Clear and intuitive control panel for advanced ease of use.



### Automatic vertical keystone correction

Images are instantly aligned with our +/- 30 degree automatic keystone correction.




### Small projector. Big impact

- Project perfect, natural images even in the lightest room with advanced 3LCD technology
- Hassle-free travelling thanks to a lightweight, portable design and carrying case
- Bright images with 2000 ANSI lumens from energy efficient, Epson exclusive E-TORL lamp
- Create a perfect 60" image from only 2 metres away
- Plug in and be ready to present in 7 seconds
- No cool off time with our instant off button
- No distraction – operates quietly with low fan noise
- Automatic image adjustment with vertical keystone correction (+/- 30°)

Epson  
EMP  
750/755

<b>Model</b>	Epson EMP-750 / Epson EMP-755
<b>Projection System</b>	Epson 3LCD Advanced Imaging Technology
<b>Projection Method</b>	Front / Rear / Ceiling Mount
<b>Specification of Main Parts</b>	
<b>LCD Panels</b>	Size: 0.7 inches with MLA; Driving Method: Poly-silicon TFT Active Matrix; Pixel Number: 786432 dots (1024x768) x3; Native Resolution: XGA; Aspect Ratio: 4:3; Pixel Arrangement: Stripe; Refresh Rate: 72Hz
<b>Projection Lens</b>	Type: Manual: zoom / focus; F-number: 1.58 to 1.76; Focal Length: 23.7mm - 28.5mm; Zoom Ratio: 1 - 1.2; Offset: 6:1; Lens Cover: Attached with cord
<b>Lamp</b>	Type: 170W UHE; Life: 2000h (High Brightness) / 3000h (Low Brightness)
<b>Screen Size</b> (Projected Distance)	30 to 300" [1.2 to 12.1m] (Zoom: Tele), 30 to 300" [1.0 to 10.1m] (Zoom: Wide)
<b>Brightness</b>	2000 ANSI lumens / 1500 ANSI lumens
<b>High/Low Brightness Mode</b>	2000 ANSI lumens / 1500 ANSI lumens
<b>Contrast</b>	400:1 (Colour Mode: Dynamic, High Brightness Mode)
<b>Brightness Uniformity</b>	90% (Typ.)
<b>Colour Reproduction</b>	Full Colour (16.77 million colours)
<b>Sound Output</b>	1W Monaural (internal speaker)
<b>Function</b>	Pointer, User Logo, A/V Mute, Freeze
<b>Colour Mode</b>	Dynamic, Presentation, Living Room, Theatre, Blackboard, sRGB
<b>Effective Scanning</b>	Pixel Clock: 13.5MHz to 162MHz
<b>Frequency Range (Analog)</b>	Horizontal: 15KHz to 92KHz; Vertical: 50Hz to 85Hz
<b>Adjustment Function</b>	Projector / Remote Control: Keystone / Brightness / Contrast / Tint / Saturation / Sound / Input Signal; Foot Adjuster: Front Centre, Rear; Tilt Angle: 0 to 12 degrees; Keystone Correction: Vertical: -30 to +30 degrees (Zoom: Tele); Auto Keystone Correction; Auto Detection of RGB/YCbCr; Operation Panel Protected Function; Security Function (Protection of User Logo, Time Lock)
<b>Analog RGB I/O</b>	
<b>Display Performance</b>	Native: XGA (1024x768 dots)
<b>Input Signal</b>	Signal Type: Separate Signal; Video Signal: Analog (0.7V p-p, 75 ohm / Mac 0.714Vp-p, 75ohm); Sync. Signal: Separate (positive & negative, bi-polarity 2-5Vpp) / Composite (positive & negative, bi-polarity 2-5Vpp) / Sync-on-green (negative, 0.3Vpp)
<b>Video Input Terminal</b>	Mini D-sub 15pin x 1 Blue-molding
<b>Video I/O</b>	
<b>Display Performance</b>	NTSC: 560 line; PAL: 560 line
<b>Input Signal</b>	Video Standard: NTSC / NTSC 4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM; Video Signal: Composite Video (1.0Vpp / Sync.negative, 75ohm) / S-Video (Luminous 0.714Vpp, Chrominous 0.286Vpp, 75ohm) / Component Video (Analog Y level 0.7V 75ohm / Cr Cb level ±0.35V 75ohm / sync.negative 0.3V or 3-state ±0.3V on Y) / Video-RGB (0.7V p-p, 75ohm / Mac 0.714Vpp, 75ohm)
<b>Video Input Terminal</b>	Composite Video: RCA (Yellow) x 1; S-Video: Mini DIN; Component Video: Mini D-sub 15pin Blue-molding (common with Analog RGB connector); Video-RGB: Mini D-sub 15pin Blue-molding (common with Analog RGB connector)
<b>Audio I/O</b>	
<b>Audio Signal</b>	500mVrms / 47Kohm
<b>Audio Terminal</b>	Stereo mini jack x 1 (Audio In or Out are selectable on OSD menu; Audio Out is available on Epson EMP-755 only)
<b>Control I/O: USB I/O</b>	I/O Terminal: USB connector series B x 1 (for mouse, K/B, control); Only on Epson EMP-755 / USB connector series A x 1 (for DSC, USB Memory)
<b>Card I/O: PCMCIA:</b>	Only on Epson EMP-755 / Type I/II x 1
<b>Operating Temperature</b>	5°C to 35°C <41°F to 95°F>
<b>Direct Power On</b>	Plug in and be ready to present in 7 seconds
<b>Start-Up/Cool-down Period</b>	7 Seconds / 0 Second (Instant Off)
<b>Power Supply Voltage</b>	100 - 240VAC ±10%, 50/60Hz AC
<b>Power Consumption</b>	230V area (Europe), Lamp on: 240W, Standby (Network on): 35W (Epson EMP-755 only), Standby (Network off): 4.0W
<b>Dimension (D x W x H)</b>	193 x 276 x 70mm (excluding feet) / 193 x 276 x 81mm (maximum)
<b>Weight</b>	Epson EMP-755: Approx. 3.9lbs / 1.8kg; Epson EMP-750: Approx. 3.8lbs / 1.7 kg
<b>Fan Noise</b>	35dB (Low Brightness Mode)
<b>Accessories</b>	Power Cord: 1.8m; Computer Cable: 1.8m Mini D-sub 15pin (Male) - Mini D-sub 15pin (Male) USB Cable: 1.8m, USB A / USB B; Remote Control: included; Battery: Alkaline AAA x 2; Audio Adapter: 3.5mm Stereo Miniplug (Male); RCA Jack x 2 (Female) 15cm; Soft Carrying Case: included; Password Protect Sticker: included; Wireless LAN Card: included 802.11g/b (Epson EMP-755 only); EasyMP software (CD-ROM): included (only on Epson EMP-755); Owner's Manual: included (CD-ROM); Quick Reference Guide: included
<b>Options</b>	Spare Lamp: ELPLP32; Air Filter Set: ELPAF08; Soft Carrying Case (for PC): ELPKS16
<b>Warranty</b>	UK: 3 year next day on-site repair or replace Ireland: 3 year next day on-site repair or loan
<b>Epson EasyMP Features</b>	Epson EMP-755 only
<b>Function</b>	Projector Control and Projector Management via Network, E-mail Notification, SNMP, Card Player (with USB storage player), Network Screen, Easy Web
<b>Software</b>	Epson EMP Monitor (for Windows), Epson EMP Network Manager (via Web site) Epson EMP NS Connection (for Windows) (New), Epson EMP NS Connection (for Mac) Epson EMP Slide Maker2
<b>Security (Wireless LAN)</b>	WPA, CCX (Cisco®)

Screen Diagonal (inches)



Projection Distance (wide/tele) (metres)



1 2 3 4 5 6

1. USB
2. Audio
3. Video
4. S-Video Input
5. RGB Input
6. USB



Telephone: +44 (0) 1442 261144  
E-mail: info@epson.co.uk

Fax: +44 (0) 8702 413093  
www.epson.co.uk